



Dispositivo di Ancoraggio per Palo Stradale su Banchina

Anchoring device for Road Pole on Shoulder



Disponibile per palo tondo e tondo antirotazione Ø 48/60/90 mm nelle varianti a 3 e 4 inserti di ancoraggio.
48/60/90 mm round pole and round anti-rotation pole available, with alternatives of 3 and 4 anchoring inserts.

- ✓ Evita scavo e plinto in calcestruzzo
- ✓ Non richiede attrezzature speciali
- ✓ Si installa in pochi secondi
- ✓ Tenuta immediata
- ✓ Non asporta terreno
- ✓ Riutilizzabile
- ✓ Facilmente smaltibile
- ✓ Applicabile:
 - in presenza di sassi e pietre
 - su banchina ridotta e s coscesa

- ✓ Avoids the excavation and the concrete footing
- ✓ No special equipment is required
- ✓ Installed in a very few seconds
- ✓ Immediately resistant to load
- ✓ No soil removal
- ✓ Reusable
- ✓ Easily disposed
- ✓ Applicabile:
 - in the presence of boulders and stones
 - under conditions of steep and reduced road shoulder



BREVETTO INTERNAZIONALE

INTERNATIONAL PATENT



APPLICAZIONI

Installazione di pali per segnaletica verticale sia di traffico che pubblicitaria e comunque di elementi verticali tubolari di sezione tonda e tonda con antirotazione. Una banchina ridotta o scoscesa non rappresenta una limitazione nell'utilizzo del dispositivo.

APPLICATIONS

Installation of pole for vertical road signalling, both for traffic signs and for advertising, and anyway for round cross section and round with anti-rotation vertical tubular elements. A reduced or steep shoulder is not a limit in using the device.



INSTALLAZIONE DEL SEGNALE IN POCHI SECONDI

(guarda il video di installazione visitando la sezione segnaletica nel nostro sito web)

- 1) Alloggiare la base a filo interno del palo e fissarla con viti auto-foranti. Sul palo può già essere montato il cartello.
- 2) Posizionare il segnale e conficcare gli inserti di ancoraggio uno alla volta monitorando la posizione verticale del palo mediante livella a bolla. Per l'introduzione degli inserti può essere utilizzato un comune martello o un martello elettropneumatico.
- 3) Ricoprire eventualmente la base di ancoraggio con la terra precedentemente spostata per un miglior risultato estetico.



SIGN INSTALLATION IN A FEW SECONDS

(watch the installation video by visiting the road sign section on our website)

- 1) House the base flush with the inner side of the pole and secure it with self-drilling screws. The sign may already be mounted on the pole.
- 2) Position the sign and drive-in the inserts one at a time by checking the vertical position of the pole through a bubble level. To drive-in the inserts, a common hammer or a jackhammer can be used.
- 3) For a better aesthetic result, cover if necessary the anchoring base with the earth previously excavated.

ACCESSORI

Sono disponibili inserti di lunghezze superiori allo standard per far fronte a terreni poco coesivi.

ACCESSORIES

To deal with soils than are not very cohesive, are available higher than standard insert lengths.

PRODUCT	Nr INS.	POLE	ACCESSORIES	Materiale
TSRS33048	3	48 mm	Ins. 75/100 cm	Zinc-coated Steel
TSRS33060	3	60 mm	Ins. 75/100 cm	Zinc-coated Steel
TSRS43060	4	60 mm	Ins. 75/100 cm	Zinc-coated Steel
TSRS44090	4	90 mm	Ins. 100/120 cm	Zinc-coated Steel

TREESYSTEM
DISPOSITIVI DI ANCORAGGIO

TreeSystem s.r.l.
Via Moraro 22, 35020, Pozzonovo (PD), Italy
Tel/fax +39 0429 773 082
info@treesystem.it - www.treesystem.it

